


CURVE DATA:

Curve Number	Delta	Radius	Area	Tangent Length	Chord Bearing	Chord Length
1	10° 16' 55"	630.00'	113.42'	85.86'	N 57° 24' 16" E	113.27'
2	87° 52' 48"	25.00'	38.34'	24.09'	S 34° 48' 47" W	34.70'
3	14° 15' 47"	970.00'	241.47'	121.36'	S 24° 44' 30" E	240.95'
4	5° 10' 15"	1830.00'	155.15'	92.63'	S 28° 11' 43" W	165.10'
5	20° 31' 28"	770.00'	343.02'	174.41'	S 18° 01' 07" W	340.19'
6	25° 53' 47"	2830.00'	132.95'	65.49'	N 05° 42' 15" E	132.93'
7	25° 53' 47"	2870.00'	129.92'	64.97'	N 05° 42' 15" E	129.90'
8	25° 51' 28"	830.00'	359.75'	186.00'	S 18° 01' 07" W	356.70'
9	14° 15' 47"	1770.00'	159.74'	79.32'	S 28° 11' 43" W	159.63'
10	10° 16' 55"	1030.00'	256.41'	128.87'	S 32° 44' 30" E	256.75'
11	10° 22' 41"	970.00'	175.70'	88.09'	S 34° 41' 03" W	175.45'
12	10° 18' 05"	1030.00'	85.17'	43.11'	S 32° 22' 06" E	85.14'
13	87° 00' 42"	25.00'	37.97'	23.73'	N 08° 44' 28" E	34.42'
14	10° 18' 05"	870.00'	102.82'	51.45'	S 27° 24' 16" E	102.46'
15	25° 53' 47"	2600.00'	131.43'	66.73'	N 05° 42' 15" E	131.41'
16	25° 51' 28"	800.00'	356.39'	181.20'	S 18° 01' 07" W	353.45'
17	5° 10' 15"	1800.00'	162.45'	81.28'	S 28° 11' 43" W	162.39'
18	14° 15' 47"	1000.00'	248.94'	125.12'	S 24° 44' 30" E	248.30'
19	10° 22' 41"	1000.00'	181.13'	90.61'	S 34° 41' 03" W	180.89'
20	10° 18' 05"	800.00'	108.02'	54.16'	S 27° 24' 16" E	107.88'
21	00° 28' 36"	1030.00'	8.57'	4.28'	N 29° 44' 00" W	8.57'
22	01° 02' 53"	2630.00'	48.11'	24.05'	N 08° 40' 36" W	48.11'

LINE DATA:

Line	Bearing	Distance
L1	S 36° 36' 36" E	47.42'
L2	S 36° 36' 36" E	47.42'
L3	S 36° 36' 36" E	47.42'
L4	S 36° 36' 36" E	47.42'
L5	S 36° 36' 36" E	47.42'
L6	S 36° 36' 36" E	47.42'
L7	S 36° 36' 36" E	47.42'
L8	S 36° 36' 36" E	47.42'
L9	S 36° 36' 36" E	47.42'
L10	S 36° 36' 36" E	47.42'

- GENERAL NOTES**
- All block corner radii are to be 25' unless otherwise indicated on this plat.
 - There is a ten (10) foot "Building Setback Line" established along all side lot lines except as otherwise indicated on this plat. Front and rear "Building Setback Lines" are as shown on the above plat and more particularly described in the Declaration of Covenants, Restrictions and Conditions for Weston Lakes, Section 8.
 - U.E. indicates "Utility Easement".
 - There are no existing pipelines or pipeline easements within the boundaries of the Subdivision.
 - There is a minimum slab elevation for each lot which shall in no case be lower than the higher of the 100-year flood plain or eighteen inches (18") above natural ground.
 - There is dedicated a thirty (30) foot aerial easement, across a twenty (20) foot utility easement and extending five (5) additional feet on either side of the twenty (20) foot utility easement that runs along the north boundary of Reserve "EE".
 - There is dedicated a twenty (20) foot utility easement along the front of all lots, except as otherwise indicated on this plat.
 - There is dedicated a twenty (20) foot utility easement along the side lot lines adjacent to the street right-of-ways of all corner lots, except as otherwise indicated on this plat.
 - There is dedicated a five (5) foot utility easement along each side of all side lot lines, except as otherwise indicated on this plat.
 - There is dedicated a twenty (20) foot maintenance easement along the rear of Lots 3 thru 18, Block 13.
 - There is also a restrictive building area along the rear of Lots 3 thru 18, Block 13 as more particularly described in the recorded restrictions for the subdivision.
 - All street right-of-ways are hereby dedicated as Utility Easements.
 - There are other dedicated Utility Easements as indicated on this plat.
 - Each lot shall be provided with an adequate culvert having a net drainage opening area of sufficient size to permit the free flow of water without backwater and in no instance have a drainage opening of less than one and three quarters (1-3/4) square feet (18" diameter), unless otherwise approved.
 - All street right-of-ways are 60-feet wide unless otherwise noted.
 - A one-foot reserve is hereby dedicated to the public in fee as a buffer separation between the side or end of streets where such streets abut adjacent acreage tracts, the condition of such dedication being that when the adjacent property is subdivided in a recorded plat, the one-foot reserve shall thereupon become vested in the public for street right-of-way purposes and the fee title thereto shall revert to and vest in the dedicator, his heirs, assigns, or successors.
 - B.M.: U.S.G.S. Monument F1280 located 4.1 miles east of Fulshear. Elevation = 127.65 feet (1978 Datum).
 - T.B.M.: Railroad spike set in 36-inch pecan tree located ±30-feet southwest of the northern most corner of Lot 17, Block 13, Weston Lakes Section 8. Elevation = 112.34 (1978 Datum).
 - B.L. indicates "Building Setback Line".
 - All easements are centered on lot lines unless shown otherwise.



ADDRESS MAP OF WESTON LAKES SECTION 8

A SUBDIVISION OF 27.235 ACRES OF LAND
OUT OF THE JOHN RANDON LEAGUE, ABSTRACT NO. 76
FORT BEND COUNTY, TEXAS

31 LOTS 1 RESERVE 3 BLOCKS

JULY, 1987

PLANNER:
WILLIAMS & CRAWFORD, INC.
2400 WEST LOOP SOUTH, SUITE 104
HOUSTON, TEXAS

OWNER:
UNITED FINANCIAL CORP.
1250 SHORELINE DRIVE
SUGARLAND, TEXAS
242-1188

ENGINEER:
J.C. JONES & CARTER, INC.
Consulting Engineers
6335 GULFTON DRIVE, SUITE 200
HOUSTON, TEXAS
777-5337

8613350
FILED FOR RECORD
TIME 12:05 P.M.
SLIDE 9814
MAR 21 1988
Dianne Miller
County Clerk, Fort Bend Co., Tex